

SOUND ANCHORS INC.
2835 KIRBY AVE. NE #110 PALM BAY FL 32905
PHONE 321-724-1237 FAX 321-914-0953

INSTRUCTIONS FOR SOUND ANCHORS B&W 802 MATRIX STANDS

Congratulations on your purchase of Sound Anchors Stands for your B&W 802 speakers. These stands are designed to enhance the performance of your audio system by placing the drivers of your speaker system at the correct height and eliminating resonances in the critical speaker to room interface. Follow these simple instructions and you will be rewarded with superior sonic results.

INVENTORY

1. Sound Anchors Stands (2)
2. Spikes (6)
3. 3/8 flatwashers (6)
4. 3/8-16 jam nuts (6)
5. M6X25 socket head cap screw (8)
6. 1/4 flat washer (8)
7. 3/16 hex key

1. Check your inventory. If anything is missing please let Sound Anchors or your dealer know.
2. Install the spikes into the threaded inserts in the bottom of the stand along with their jam nuts and flat washers.
3. Place your stands in the approximate position where your speakers will be for listening purposes.
4. Place the speakers on top of the stands so the inserts on bottom corners of speakers line up with slots in mounting brackets on the top of the stands.
5. Install M6 socket head cap screws with flatwashers into the inserts on bottom of the speakers.
FINGER TIGHTEN ONLY!
6. Use the supplied hex key to tighten the socket screws. **CAUTION!** do not over tighten as speaker damage may result.
7. You may now final position your speakers by walking them on the cones. This is the preferred method of moving the speaker-stand combination.